

Package: flowcluster (via r-universe)

May 19, 2026

Title Cluster Origin-Destination Flow Data

Version 0.2.1.9000

Description Provides functionality for clustering origin-destination (OD) pairs, representing desire lines (or flows). This includes creating distance matrices between OD pairs and passing distance matrices to a clustering algorithm. See the academic paper Tao and Thill (2016) <[doi:10.1111/gean.12100](https://doi.org/10.1111/gean.12100)> for more details on spatial clustering of flows. See the paper on delineating demand-responsive operating areas by Mahfouz et al. (2025) <[doi:10.1016/j.urbmob.2025.100135](https://doi.org/10.1016/j.urbmob.2025.100135)> for an example of how this package can be used to cluster flows for applied transportation research.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

URL <https://hussein-mahfouz.github.io/flowcluster/>,
<https://github.com/hussein-mahfouz/flowcluster>

Depends R (>= 4.1.0)

Imports sf, dbscan, dplyr, glue, lwgeom, purrr, rlang, tibble, units, tidyr, tidyselect

LazyData true

Suggests testthat (>= 3.0.0), tmap

Config/testthat/edition 3

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev libicu-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://hussein-mahfouz.r-universe.dev>

Date/Publication 2025-08-22 08:41:39 UTC

RemoteUrl <https://github.com/hussein-mahfouz/flowcluster>

RemoteRef HEAD

RemoteSha a7467fff310927e2c71c9b4c7b133f730c469c56

Contents

add_flow_length	2
add_xyuv	3
aggregate_clustered_flows	3
cluster_flows_dbscan	5
dbscan_sensitivity	6
distance_matrix	7
filter_by_length	8
flow_distance	9
flows_leeds	10
weight_vector	10
Index	12

add_flow_length	<i>Add Length Column to Flow Data</i>
-----------------	---------------------------------------

Description

Also checks that 'origin' and 'destination' columns are present.

Usage

```
add_flow_length(x)
```

Arguments

x sf object of flows (LINESTRING, projected CRS)

Value

sf object with an additional length_m column (od length in meters)

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- add_flow_length(flows)
```

add_xyuv	<i>Add Start/End Coordinates & Flow IDs</i>
----------	---

Description

Add Start/End Coordinates & Flow IDs

Usage

```
add_xyuv(x)
```

Arguments

x sf object of flows

Value

tibble with x, y, u, v, flow_ID columns

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- add_flow_length(flows)
flows <- add_xyuv(flows)
```

aggregate_clustered_flows	<i>Aggregate clustered OD flows into representative lines</i>
---------------------------	---

Description

This function aggregates flows within clusters and creates a single representative line for each cluster. The start and end coordinates are computed as weighted averages (weighted by flow counts or another variable), or simple means if no weights are provided. Each cluster is represented by one LINESTRING.

Usage

```
aggregate_clustered_flows(flows, weight = NULL, crs = sf::st_crs(flows))
```

Arguments

flows An sf object containing OD flows with coordinates for origins (x, y) and destinations (u, v), a cluster column, and optionally a count or other weighting variable.

weight (optional) Name of a column in flows to use for weighting. If NULL (default), unweighted means are used.

crs Coordinate reference system for the output (default: taken from flows).

Value

An sf object with one line per cluster, containing:

- `count_total`: total weight (if provided), otherwise number of flows
- `size`: the cluster size (from the input, not recomputed)
- `geometry`: a LINESTRING representing the aggregated OD flow

Examples

```
# ----- 1. Basic Usage: A quick, runnable example ---
# This demonstrates the function with minimal, fast data preparation.
flows <- flowcluster::flows_leeds

# Create the required input columns in a single, fast pipeline
flows_clustered <- flows |>
  add_xyuv() |>
  # Manually create 3 dummy clusters for demonstration
  dplyr::mutate(cluster = sample(1:3, size = nrow(flows), replace = TRUE)) |>
  # The function requires a 'size' column, so we add it
  dplyr::group_by(cluster) |>
  dplyr::add_tally(name = "size") |>
  dplyr::ungroup()

# Demonstrate the function
flows_agg_w <- aggregate_clustered_flows(flows_clustered, weight = "count")
print(flows_agg_w)

# ----- 2. Detailed Workflow (not run by default) ---
## Not run:
# This example shows the ideal end-to-end workflow, from raw data
# to clustering and finally aggregation. It is not run during checks
# because the clustering steps are too slow.

# a) Prepare the data by filtering and adding coordinates
flows_prep <- flowcluster::flows_leeds |>
  sf::st_transform(3857) |>
  add_flow_length() |>
  filter_by_length(length_min = 5000, length_max = 12000) |>
  add_xyuv()

# b) Calculate distances and cluster the flows
distances <- flow_distance(flows_prep, alpha = 1.5, beta = 0.5)
dmat <- distance_matrix(distances)
wvec <- weight_vector(dmat, flows_prep, weight_col = "count")
flows_clustered_real <- cluster_flows_dbscan(dmat, wvec, flows_prep, eps = 8, minPts = 70)

# c) Filter clusters and add a 'size' column
flows_clustered_real <- flows_clustered_real |>
  dplyr::filter(cluster != 0) |> # Filter out noise points
  dplyr::group_by(cluster) |>
  dplyr::mutate(size = dplyr::n()) |>
  dplyr::ungroup()
```

```
# d) Now, use the function on the clustered data
flows_agg_real <- aggregate_clustered_flows(flows_clustered_real, weight = "count")
print(flows_agg_real)

# e) Visualize the results
if (requireNamespace("tmap", quietly = TRUE)) {
  library(tmap)
  # This plot uses modern tmap v4 syntax.
  tm_shape(flows_clustered_real, facet = "cluster") +
    tm_lines(col = "grey50", alpha = 0.5) +
  tm_shape(flows_agg_real) +
    tm_lines(col = "red", lwd = 2) +
  tm_layout(title = "Original Flows (Grey) and Aggregated Flows (Red)")
}

## End(Not run)
```

cluster_flows_dbscan *Cluster Flows using DBSCAN*

Description

See [dbscan](#) for details on the DBSCAN algorithm.

Usage

```
cluster_flows_dbscan(dist_mat, w_vec, x, eps, minPts)
```

Arguments

dist_mat	distance matrix
w_vec	weight vector
x	flows tibble with flow_ID
eps	DBSCAN epsilon parameter
minPts	DBSCAN minPts parameter

Value

flows tibble with an additional cluster column

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- head(flows, 100) # for testing
# Add flow lengths and coordinates
flows <- add_flow_length(flows)
# filter by length
```

```
flows <- filter_by_length(flows, length_min = 5000, length_max = 12000)
flows <- add_xyuv(flows)
# Calculate distances
distances <- flow_distance(flows, alpha = 1.5, beta = 0.5)
dmat <- distance_matrix(distances)
wvec <- weight_vector(dmat, flows, weight_col = "count")
clustered <- cluster_flows_dbscan(dmat, wvec, flows, eps = 8, minPts = 70)
```

dbscan_sensitivity *Sensitivity analysis of DBSCAN parameters for flow clustering.*

Description

The function allows you to test different combinations of epsilon and minPts parameters for clustering flows using DBSCAN. It can be used to determine what parameter values make sense for your data

Usage

```
dbscan_sensitivity(
  dist_mat,
  flows,
  options_epsilon,
  options_minpts,
  w_vec = NULL
)
```

Arguments

dist_mat	a precalculated distance matrix between desire lines (output of distance_matrix())
flows	the original flows tibble (must contain flow_ID and 'count' column)
options_epsilon	a vector of options for the epsilon parameter
options_minpts	a vector of options for the minPts parameter
w_vec	Optional precomputed weight vector (otherwise computed internally from 'count' column)

Value

a tibble with columns: id (to identify eps and minpts), cluster, size (number of desire lines in cluster), count_sum (total count per cluster)

Examples

```

flows <- sf::st_transform(flows_leeds, 3857)
flows <- head(flows, 1000) # for testing
# Add flow lengths and coordinates
flows <- add_flow_length(flows)
# filter by length
flows <- filter_by_length(flows, length_min = 5000, length_max = 12000)
# Add x, y, u, v coordinates to flows
flows <- add_xyuv(flows)
# Calculate distance matrix
distances <- flow_distance(flows, alpha = 1.5, beta = 0.5)
dmat <- distance_matrix(distances)
# Generate weight vector
w_vec <- weight_vector(dmat, flows, weight_col = "count")

# Define the parameters for sensitivity analysis
options_epsilon <- seq(1, 10, by = 2)
options_minpts <- seq(10, 100, by = 10)
## Run the sensitivity analysis
results <- dbscan_sensitivity(
  dist_mat = dmat,
  flows = flows,
  options_epsilon = options_epsilon,
  options_minpts = options_minpts,
  w_vec = w_vec
)

```

distance_matrix

Convert Long-Format Distance Tibble to Matrix

Description

Convert Long-Format Distance Tibble to Matrix

Usage

```
distance_matrix(distances, distance_col = "fds")
```

Arguments

distances tibble with columns flow_ID_a, flow_ID_b, and distance
distance_col column name for distance (default "fds")

Value

distance matrix (tibble with rownames). The matrix has flow_ID_a as rownames and flow_ID_b as column names. This function converts the output of flow_distance() into a format suitable for the [dbscan](#) clustering algorithm.

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- head(flows, 100) # for testing
# Add flow lengths and coordinates
flows <- add_flow_length(flows)
flows <- add_xyuv(flows)
# Calculate distances
distances <- flow_distance(flows, alpha = 1.5, beta = 0.5)
dmat <- distance_matrix(distances)
```

filter_by_length	<i>Filter Flows by Length</i>
------------------	-------------------------------

Description

Filter Flows by Length

Usage

```
filter_by_length(x, length_min = 0, length_max = Inf)
```

Arguments

x	sf object with length_m
length_min	minimum length (default 0)
length_max	maximum length (default Inf)

Value

filtered sf object. Flows with length_m outside the specified range are removed.

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- add_flow_length(flows)
flows <- filter_by_length(flows, length_min = 5000, length_max = 12000)
```

flow_distance	<i>Calculate Flow Distance and Dissimilarity</i>
---------------	--

Description

This function calculates flow distance and dissimilarity measures between all pairs of flows based on the method described in @tao2016spatial.

Usage

```
flow_distance(x, alpha = 1, beta = 1)
```

Arguments

x	tibble with flow_ID, x, y, u, v, length_m
alpha	numeric, origin weight
beta	numeric, destination weight

Value

tibble of all OD pairs with fd, fds columns

References

Tao, R., Thill, J.-C., 2016. Spatial cluster detection in spatial flow data. *Geographical Analysis* 48, 355–372. <https://doi.org/10.1111/gean.12100>

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- head(flows, 100) # for testing
# Add flow lengths and coordinates
flows <- add_flow_length(flows)
flows <- add_xyuv(flows)
# Calculate distances
distances <- flow_distance(flows, alpha = 1.5, beta = 0.5)
```

flows_leeds	<i>Example flow data for Leeds. It is from the 2021 census, and it contains all Origin - Destination flows at the MSOA level. For more info on census flow data, see the Rhrefhttps://www.ons.gov.uk/census/aboutcensus/censusproducts/origindestinationflowdataONS documentation See data-raw/flows_leeds.R for how this data was created.</i>
-------------	---

Description

Example flow data for Leeds. It is from the 2021 census, and it contains all Origin - Destination flows at the MSOA level. For more info on census flow data, see the [ONS documentation](#) See data-raw/flows_leeds.R for how this data was created.

Usage

```
flows_leeds
```

Format

An object of class `sf` with `LINESTRING` geometry. It has the following columns:

origin MSOA code of origin zone

destination MSOA code of destination zone

count number of people moving from origin to destination

geometry desire line between origin and destination

Source

https://www.nomisweb.co.uk/sources/census_2021_od

weight_vector	<i>Generate Weight Vector from Flows</i>
---------------	--

Description

Generate Weight Vector from Flows

Usage

```
weight_vector(dist_mat, x, weight_col = "count")
```

Arguments

<code>dist_mat</code>	distance matrix
<code>x</code>	flows tibble with <code>flow_ID</code> and <code>weight_col</code>
<code>weight_col</code>	column to use as weights (default = "count")

Value

numeric weight vector. Each element corresponds to a flow in the distance matrix, and is used as a weight in the DBSCAN clustering algorithm.

Examples

```
flows <- sf::st_transform(flows_leeds, 3857)
flows <- head(flows, 100) # for testing
# Add flow lengths and coordinates
flows <- add_flow_length(flows)
flows <- add_xyuv(flows)
# Calculate distances
distances <- flow_distance(flows, alpha = 1.5, beta = 0.5)
dmat <- distance_matrix(distances)
wvec <- weight_vector(dmat, flows, weight_col = "count")
```

Index

* datasets

- flows_leeds, [10](#)

- add_flow_length, [2](#)
- add_xyuv, [3](#)
- aggregate_clustered_flows, [3](#)

- cluster_flows_dbscan, [5](#)

- dbscan, [5](#), [7](#)
- dbscan_sensitivity, [6](#)
- distance_matrix, [7](#)

- filter_by_length, [8](#)
- flow_distance, [9](#)
- flows_leeds, [10](#)

- sf, [10](#)

- weight_vector, [10](#)